



Remark) 1. Co-planarity is within 0.08mm
 2. Plating
 Contact area: Palladium-Nickel 0.75 to 1.5 µm + Gold 0.05 to 0.15 µm
 Lead area: Gold 0.05 to 0.15 µm
 Under plating: Nickel 2 to 3 µm
 3. Opening area shape: Conform to USB2.0 standard
 4. Per reel: 3000 pcs

3	Stainless-Steel	Gold 0.01 µm min. (Selective mating and soldering area) Lubricant	5	PE	Top cover tape
2	Copper-Alloy	2	4	PS	Embossed carrier tape
1	LCP	Black UL94V-0			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 5 : 1	COUNT	DESCRIPTION OF REVISIONS	
DESIGNED		CHECKED		DATE	
APPROVED : A0. SUZUKI		10.11.12		DRAWING NO. EDC3-127248-00	
CHECKED : RI. TAKAYASU		10.11.12		PART NO. ZX62WRD-B-5PC	
DESIGNED : TA. TORIHARA		10.11.12		CODE NO. CL242-0059-1-00	
DRAWN : TA. TORIHARA		10.11.12		1/1	