

SUMMARY

Wires

Low	19
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series	C
Termination type	Female solder
IP rating	50
Cable Ø	7.30 - 9.20 mm
Matching parts	CAB.M19.GLA.C92GZ
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	CR*: Free receptacle with cable collet and nut for fitting a bend relief
Keying	2 keys (gamma=60; Plug: male contacts; Receptacle: female contacts)
Housing Material	PSU (Polysulfone), gray
Cable Fixing	∅ 7.3 - 9.2 mm
Variant	

Performance

Configuration	
Insulator	
Rated Current	5 Amps

Specifications

Test voltage (kV rms) Contact-contact:	1.4
Air clearance min. (mm) or Creepage distance min. (mm):	0.6


Others

F ret (min):	150 N
--------------	-------

F ret (max): 250 N
Steam sterilization: 20 times
IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L
mm.	18	56
in.	0,71	2,20

RECOMMENDED BY LEMO

Tools

None

Cables