

# Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 335/12.5/1+0 - 2801041

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Universal varistor-based plug-in lightning/surge arrester for 1-phase power supply networks with common N and PE (2-conductor system: L1, PEN).

## Why buy this product

- ✓ Plugs can be checked with CHECKMASTER
- ✓ Secure hold of plugs in the event of high lightning current loads and strong vibrations thanks to new latching
- ✓ Thermal disconnect device for each individual plug
- ✓ Pluggable
- ✓ Thermal disconnect device for each individual plug
- ✓ Mechanical coding of all slots

RoHS

## Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 698108
GTIN	4046356698108

## Technical data

### Dimensions

Height	90 mm
Width	17.5 mm
Depth	77.5 mm
Horizontal pitch	1 Div.

### Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl (above mean sea level))

# Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 335/12.5/1+0 - 2801041

## Technical data

### Ambient conditions

Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (half sinus / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

### General

IEC test classification	I / II
	T1 / T2
	T1
EN type	T1 / T2
	T1
IEC power supply system	TN-S
	TN-C
	TT
Mode of protection	L-N
	L-PEN
Mounting type	DIN rail: 35 mm
Color	jet black RAL 9005
Housing material	PA 6.6
	PBT
Degree of pollution	2
Flammability rating according to UL 94	V-0
Design	DIN rail module, two-section, divisible
Surge protection fault message	optical

### Protective circuit

Nominal voltage $U_N$	240 V AC (TN-C, TN-S)
	240 V AC (TT)
Nominal frequency $f_N$	50 Hz (60 Hz)
Maximum continuous voltage $U_C$	335 V AC
Rated load current $I_L$	80 A
Residual current $I_{PE}$	$\leq 800 \mu A$
Standby power consumption $P_C$	$\leq 270 \text{ mVA}$
Nominal discharge current $I_n$ (8/20) $\mu s$	12.5 kA
Maximum discharge current $I_{max}$ (8/20) $\mu s$	50 kA
Impulse discharge current (10/350) $\mu s$ , charge	6.25 As
Impulse discharge current (10/350) $\mu s$ , specific energy	39 kJ/ $\Omega$
Impulse discharge current (10/350) $\mu s$ , peak value $I_{imp}$	12.5 kA
Total discharge current $I_{total}$ (8/20) $\mu s$	12.5 kA
Total discharge current $I_{total}$ (10/350) $\mu s$	12.5 kA
Short-circuit current rating $I_{SCCR}$	25 kA

# Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 335/12.5/1+0 - 2801041

## Technical data

### Protective circuit

Voltage protection level $U_p$	$\leq 1.2$ kV
	$\leq 1.6$ kV (30 kA - 8/20 $\mu$ s)
Residual voltage $U_{res}$	$\leq 1.2$ kV (at $I_n$ )
	$\leq 1.1$ kV (at 10 kA)
	$\leq 1$ kV (at 5 kA)
	$\leq 0.9$ kV (at 3 kA)
TOV behavior at $U_T$	415 V AC (5 s / withstand mode)
Response time $t_A$	$\leq 25$ ns
Max. backup fuse with branch wiring	160 A (gG)
Max. backup fuse with V-type through wiring	80 A (gG - 16 mm <sup>2</sup> )

### Connection data


Connection method	Screw connection
Screw thread	M5
Tightening torque	4.5 Nm
Stripping length	16 mm
Conductor cross section flexible	1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>
Conductor cross section solid	1.5 mm <sup>2</sup> ... 35 mm <sup>2</sup>
Conductor cross section AWG	15 ... 2

### Standards and Regulations


Standards/regulations	IEC 61643-11 2011
	EN 61643-11 2012

## Drawings

Circuit diagram



Dimensional drawing



## Approvals

Approvals

## Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 335/12.5/1+0 - 2801041

### Approvals

---

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		RU C- DE.A*30.B01561
-----	---	-------------------------

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>